




Mercedes-Benz



Roadvac's Ltd

Vehicle Mercedes-Benz Arocs 5 3246 L 8x4 fact. w/base


Vehicle to standard specification

Plus options selected as listed below :

- A1E Front axle 9.0 t
- A4T Trailing axle, 8 t, steered, de-loadable, liftable
- B2Z Parking brake, additional on front axle
- B4Z Air reservoir, additional
- C0Q Frame overhang 1500 mm
- C2I Wheelbase 4200 mm
- C5A ADR chassis
- C5H Attachment fixtures, rigid
- C5P Bolted frame
- C6U Extra anti-roll bar, rear/trailing axle
- C8B Rear wing, 2550 mm vehicle width
- C8H Wing, 3-piece, with EC splash guard
- D1P Co-driver's suspension seat, comfort
- D2M Co-driver's seat backrest, release mechanism
- D2N Driver's seat backrest, release mechanism
- D2W Armrests on both sides, co-driver's seat
- D3A Luxury bed, top, wide, with levelling control
- D3B Luxury bed, bottom
- D5Z Carpet, engine tunnel
- D6I Residual engine heat utilisation
- D6M Auxiliary hot water heater, cab
- D6Z Construction-site filter
- D7G Stowage compartment lid, driver and co-driver side
- D7J Drawers, under bed
- D7V Table, on co-driver's side
- D8N Tilting sunroof, electric
- D9BC10 Omission Stowage facility, high/low, on eng. tunnel
- E1C Batteries 2 x 12 V/220 Ah, low-maintenance
- E1M Alternator, 28 V/150 A
- E3E Additional socket, 12 V/15 A, co-driver footwell
- E3R Power socket, 24 V/25 A, co-driver footwell
- E3W PSM, 2nd generation
- E4B Interface, fleet management system FMS
- E4C Additional functions, for body manufacturer
- E4Y Starting-off aid, time limit 120 s
- E5B No. 2 switch, for non-MB body electrics
- E5C No. 3 switch, for non-MB body electrics
- E5G Battery disconnect switch outside, on frame
- E5V ADR type class FL, incl. EX/II, EX/III and AT
- E6Y Reverse warning, comb. with hazard warning lights
- E9G Provision for fitting electrical devices
- F0Y Mirror cover, construction vehicle
- F1H L-cab BigSpace, 2.50 m, level floor
- F1R L-cab
- F2A Floor variant, flat floor
- F2H Cab width 2.50 m
- F2P Cab, 765 mm attachment height
- F2V BigSpace
- F3B Cab mountings, comfort, steel-sprung



Mercedes-Benz



Roadvacs Ltd

- F4X Stowage compartment exterior flap, left
- F4Y Stowage compartment exterior flap, right
- F5L Sun visor, exterior, transparent
- F7T Door extension
- F7Y Cab entrance, left/right, movable
- F8H 2 remote control keys, additional
- F9FC4O Omission MirrorCam
- J2U Navigation system
- J3Z Axle load measuring device
- J6C Multimedia Cockpit, interactive
- J6Y Remote Online
- J6Z Preinstallation Mercedes-Benz Truck App Portal
- J9P Pre-installation and display for up to 4 cameras
- K1L Tank, 430 l, left, 650 x 700 x 1100 mm, aluminium
- K5Q Fuel screen, tank filler neck
- K7B Exhaust syst., outlet downwards, fans out to right
- L1I Fog lamps, LED daytime running lamps
- L1Q Tail lights, construc. in metal holder with grille
- L4Z Protective grille, metal, for headlamps
- L9A Pre-installation for rotating beacons
- L9C Pre-installation for additional headlamps, roof
- L9G Pre-installation for flood lamp, cab rear wall
- L9AC2O Omission, daytime driving lamps
- M8B Air intake behind cab, mounted
- N1J PTO MB 123-10c, MPA, low/medium-speed
- Q1Y Front spring, 9.0 t, 4-leaf
- Q3Z Lowered frame, with residual bellow pressure ctrl.
End cross member, neutral position
- R1T 15-degree tapered rims, 11.75 x 22.5, front axle
- R1Z 15-degree tapered rims, 11.75 x 22.5, trail. axle
- S8H Fire extinguisher, 6 kg
- W7K Weight variant 37.0 t (9.0/10.5/10.5/8.0)
- Y1X Pull-out refrigerator, under bed
- Y4X Tyre inflating hose, 25 m
- Z4R Tank cross-section, high
- Z5M PTO, single
- Z5S Power take-off, pump, under top edge of frame

PDI

Delivery/handover

Transport from Rotterdam to Rolba Sweden

Stocking charge

1.2m four module LED amber flashing roof bar (Mertrux workshop)

3000w 24v to 240amp inverter (Mertrux workshop)

supply and fit micowave in centre roof locker (Mertrux workshop)

Four way camera system with DVR recording(mertrux workshop)

Audible left turn warning with side scanners (mertrux workshop)

Painting:

Cab MB 9040 jet black

Tyres:

Bridgestone 385/65 R 22,5


Bridgestone 315/80 R 22,5

Bridgestone 315/80 R 22,5

Bridgestone 385/65 R 22,5



Mercedes-Benz



Roadvacs Ltd

Removed or Replaced Standard Options :

A1D Front axle 8.0 t

D7P Tray, low, on engine tunnel

E4W Starting-off aid, speed limit 30 km/h

F6T MirrorCam

F8F Extended central locking

J6B Multimedia Cockpit

L1B Daytime driving lamps

Q1N Front spring, 8.0 t, 3-leaf

W6H Weight variant 34.5 t (8,0/9,5/9,5/7,5)

Y4Y Tyre inflating hose